

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 September 2006 (28.09.2006)

PCT

(10) International Publication Number
WO 2006/100505 A2

(51) International Patent Classification:
G06F 3/023 (2006.01)

(21) International Application Number:
PCT/GB2006/001090

(22) International Filing Date: 23 March 2006 (23.03.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0505942.3 23 March 2005 (23.03.2005) GB

(71) Applicant (for all designated States except US): **KEY-POINT TECHNOLOGIES (UK) LIMITED [GB/GB]**;
1 Ainslie Road, Hillington Park, Glasgow G52 4RU (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MOTAPARTI, Sunil [IN/GB]**; Flat 0/1, 337 Glasgow Harbour Terraces, Glasgow G11 6BH (GB). **PATEL, Sanjay [GB/GB]**; 53 Dovercourt Avenue, Thornton Heath, Surrey CR7 7LJ (GB).

(74) Agent: **ANDERSON, Angela; Murgitroyd & Company**, Scotland House, 165-169 Scotland Street, Glasgow G5 9PL (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HUMAN-TO-MOBILE INTERFACES



Mobile Phone with Basic Physical PIRS features
(PIRS & MT-IDICT Software Contained within the Device)

(57) Abstract: A method of character recognition for a mobile telephone data input apparatus comprising a plurality of data input keys having multi-character indicia, said method adapted to facilitate a reduction in the number of user interactions required to create a given data string to less than the number of characters within said data string, the method comprising the following steps: storing a set of data strings each with a priority indicator associated therewith, wherein the indicator is a measure of a plurality of derivatives associated with the data string; recognising an event; looking up the most likely subsequent data string to follow the event from the set of data strings based on one or more of the plurality of derivatives; ordering the data strings for display based on the priority indicator of that data string; if the required subsequent data string is included in the list selecting the required subsequent data string; if the required subsequent data string is not included in the list entering a event and repeating steps b to e; updating the priority indicator of the selected data string; updating the set of data strings based on the updated priority indicator.

Human-to-Mobile Interfaces

The present invention relates to human-to-mobile
5 interfaces and particularly, but not exclusively, to data
input apparatus and to an interface system, both for
facilitating a reduction in the number of key presses
required to create a data string (i.e. mnemonics,
abbreviations, words, sentences etc.) on a mobile
10 telephone or device equivalent.

Conventional mobile technologies (MT) include basic
keypads, navigation means and screen components. The
integration of various other add-on accessories into the
device, or the connections of external accessories are
15 also possible.

Conventional keypads consist of alphanumeric
telephone keys (as shown in Fig. 1); dynamic menu keys
that correspond to displayed options controlled and
varied by software; and back and cancel keys. Some mobile
20 devices have attachable foldaway or built-in QWERTY or
similar keyboards with individual keys for each
alphanumeric legend.

Navigation systems include joysticks or cursor keys
which can move or indicate left, right, up, down,
25 circular clockwise, circular anti-clockwise, and an
activation press down (i.e. trigger-down like a button)
either via a direct vertical trigger-down or relative to
the motion of navigation trigger-down. A press down
activity is a trigger for an event to occur or to be
30 processed by the resident or currently active software
systems.

Standard to mobile technologies (MT), are display
screens providing displays in either text form or graphic
form. The latter is predominant in Smart Phones and PDA
35 systems and provides a versatile Graphical User Interface

(GUI) required for the sophisticated software that is usually installed within advanced MT devices.

Other physical aspects can be included that correspond to various other software features. These features run in conjunction with embedded hardware or firmware such as infrared transmitters or wireless/radio transmitters, or connectivity interfaces that enable extension modules such as portable keyboards, computer docking or hands-free accessories to be integrated into or connected to the MT device. Camera systems are also prevalent on MT devices. Touch-pads or touch-screens are also available on MT devices, such as PDA systems.

For mobile telephones in particular, current data-input means are extremely limiting, arduous and inefficient. For example, a user must repeatedly press the same key on a keypad in order to scroll sequentially through each alphanumeric option until the desired character is highlighted or displayed. For example, to display the letter 'b', key '2' must be pressed twice. This method must be repeated for every character required in the composition of a desired word. Despite advancements in mobile telephone performance and handset sizing, data inputting means have remained largely unchanged for over 40 years.

Short Message Service (SMS) text messages allow mobile telephone users to send short alphanumeric messages to other mobile telephones that support the SMS utility. The huge use of SMS Texting has created diverse dictionaries of shortcuts, acronyms, abbreviations, emoticons and conversions of words and phrases, each with the aim of reducing the number of key presses required to convey information. For example, "are you free to chat" may be abbreviated to "ruf2c" to reduce the number of key presses.

To type the following SMS text message "Dear Friend, Please call me as soon as possible to fix a date for another meeting", extensive and repetitive keying is required as depicted in Fig. 2. Upper casing of letters
5 (Key '*'x3=3), general punctuation (Key '1'x2=2) and spacing between words (Key '#'x15=15) accounts for an additional +20 key presses.

When the same key needs to be used successively to access another alphanumeric character assigned to the
10 same key, a pause is required to register the first selection before continuing with accessing the following selection. This is because conventional systems need to distinguish between a user's intention to select the highlighted alphanumeric character and a user's intention
15 to continue scrolling through the assigned alphanumeric characters to access an alternative character ascribed to that same key.

The difficulty with SMS text messaging dictionaries is that they use colloquial or slang terms and are
20 therefore largely user specific. One colloquial or slang term may not be easily understood by another user, and different users tend to create different shortcuts for the same word or phrase. There is no consistency in SMS text messaging dictionaries because they are not
25 standard, regulated or shared on a consistent basis. Instead, they have become customised on a regional and per user or per language basis.

Although SMS text messaging is a modern idiom, it does provide critical communication means for people with
30 disabilities, particularly those who have hearing disabilities.

Human-to-Mobile Interfaces (HMI) need to change in order to fulfil the capacity at which the technology permits optimal use of itself. In particular, there is a
35 need for a human-to-mobile interface which reduces actual

physical interactivity (i.e. data input or key presses) while still using existing keyboards, keypads or other conventional input methods or mediums. In this way, a cost effective means to evolve interface methods

5 progressively into the next generation of more advanced and more efficient HMI systems will be achieved.

According to one aspect of the present invention there is a method of character recognition for a mobile telephone data input apparatus comprising a plurality of
10 data input keys having multi-character indicia, said method adapted to facilitate a reduction in the number of user interactions required to create a given data string to less than the number of characters within said data string, the method comprising the following steps:
15 storing a set of data strings each with a priority indicator associated therewith, wherein the indicator is a measure of a plurality of derivatives associated with the data string;
recognising an event;
20 looking up the most likely subsequent data string to follow the event from the set of data strings based on one or more of the plurality of derivatives;
ordering the data strings for display based on the priority indicator of that data string;
25 if the required subsequent data string is included in the list selecting the required subsequent data string;
if the required subsequent data string is not included in the list entering a event and repeating steps to determine the required subsequent data string;
30 updating the priority indicator of the selected data string;
updating the set of data strings based on the updated priority indicator.

According to a second aspect of the present
35 invention there is provided a character recognition

apparatus for a mobile telephone comprising a plurality of data input keys having multi-character indicia, said apparatus adapted to facilitate a reduction in the number of user interactions required to create a given data string to less than the number of characters within said data string, the apparatus comprising:

5 a memory for storing a set of data strings each with a priority indicator associated therewith, wherein the indicator is a measure of a plurality of derivatives associated with the data string;

10 an event recognition module for recognising an event; means for looking up the most likely subsequent data string to follow the event from the set of data strings based on one or more of the plurality of derivatives;

15 display means for displaying a list the most likely subsequent data string in an order based on the priority indicator of that data string;

means for selecting the required subsequent data string if it is included in the list;

20 data entry means for entering an event;

means for updating the priority indicator of any selected data string and the set of data strings based on the updated priority indicator.

The present invention describes a system that

25 attempts to reduce the number of physical interactions required to create a data string, based on etymological and ontological derivatives extracted from dynamic qualitative and quantitative information corresponding to sub-data strings stored in data dictionaries.

30 The described system operates through selection of data strings as input rather than the repetitive interactions required by existing systems for text entry or guiding prediction.

Physical interactions include but are not limited

35 to key presses, taps or handwriting gestures.

Derivatives include but are not limited to timestamp, cognitive coherence, perceptual indices, associative indices, grammar orients, correlative weights, inference ratios and pattern factorisation, etc.

5 that represent the adaptive intelligence of the system.

Qualitative and quantitative information stored includes but is not limited to (i) statistical information relating to a data string's historical usage or selection (i.e. frequency of use/selection, character
10 length, lexical pattern density/versatility, chronological weight and direction/operational indicators etc.); (ii) probability information relating to a data string's historical usage (i.e. occurrence and/or association ratios of two or more sub-data strings within
15 a longer data string; context ratios determining the likelihood of a given data string being grouped with one or more other sub-data strings to determine the context of a longer data string; (iii) run-time analytics (scaling patterns of use, historical usages,
20 contextualization, associations and occurrences thereof); (iv) dictionary priority; (v) dictionary chains (where each chain also retains and uses the information in (i), (ii) and (iii) above); (vi) data string maps between other data strings (where each map also retains and uses
25 the information in (i), (ii) and (iii) above); and (vii) translations.

The qualitative and quantitative information could be populated before the system is used and/or populated and manipulated by the user. The system could extract the
30 required qualitative and quantitative information from documents or other data collections relevant to the user. Thus the system can acclimatize to user language traits at any stage.

The qualitative and quantitative information stored in the dictionaries is updated whenever the system is used.

The qualitative and quantitative information could
5 be synchronized between two or more interface systems by means of wired or wireless connectivity. Qualitative and Quantitative information could also be synchronized between two or more interface systems by downloading from and uploading to a common database.

10 The system can handle multiple data dictionaries at the same time.

The current invention presents an interface system capable of displaying a representation of a plurality of data input keys having multi-character indicia which are
15 receptive to keyed or tapped input. The multi-character indicia are dynamically selected to accord with a statistical extrapolation of the most used alphanumerical character combinations in a given language or for a particular user.

20 The present invention saves time required for entering a data string.

The present invention empowers usability of mobile devices and thereby, unleashes their capabilities.

The current invention describes a system that
25 provides other physical interactivity reduction features (in addition to providing data strings for selection). These include but are not limited to (i) automatically entering a space after a selected data string; (ii) automatically performing forward or backward translations
30 between mnemonics or abbreviations or acronyms and their corresponding full data strings; (iii) automatically providing alternate suggestions such as synonyms, antonyms, corrections for spelling errors, etc. (iv) providing options to launch applications that are mapped
35 to certain macros, etc.

The current invention describes a system that provides means to the user for configuring all the qualitative and quantitative parameters involved in generating and displaying all the data strings meant for subsequent selection by the user.

The current invention describes a system that can also function as a remote-input mechanism for other personal computing devices.

The current invention describes a system that validates all the other specified claims in a language-independent manner.

The current invention describes a system provides mechanisms or Application Programming Interfaces (API) that allows other software systems to utilise and benefit from all the features of this invention, and to enable improved experiences for the user with such software systems. Additional to this, the API allows other software systems data storage or information repositories to be handled by this invention in similar manner to its own dictionaries etc.

The current system derivatives can be applied to any set of patterns, including but not limited to other world languages.

Differentiation of current system against existing frequency based predictive systems can be made by distinguishing (i) number of factors used in determining suggestions, (ii) factors in current system themselves represent varied properties at any one time including but not limited to discrete values, (iii) factors in current system can be at any one time rules, discrete or continuous statistics, indicators or directive placements, (iv) the current system provides suggestions by evaluating candidates using a dynamic weighing scheme that determined by the inter-relationships of the weighing factors at any one time, (v) current system is a

selective input system with absolute keying for refining the projection of suggestions.

Existing prediction systems do not consider the nature of language composition. They solely rely on the frequency of particular words in making predictions and are oblivious to the need of the composition. The current invention attempts to capture the essence of language composition in a dynamic and natural way. The spirit of language composition lies in realizing the importance of context, grammar and semantics. The contributions of context, grammar and semantics are captured by the etymological and ontological derivatives used by the current invention. These derivatives are applied in parallel or sequentially. The derivatives are all inter-related and therefore, can affect their own weight or the weight of other derivatives during execution, resulting in a dynamic weighing scheme. The current invention provides suggestions by evaluating candidates using the dynamic weighing scheme. For example, in a scenario involving three derivatives (say grammar orients, associative indices and contextual ratios), the grammar orients enforces the type (part-of-speech) of suggestion in light of the composition and overall syntax. There are many possibilities for the part-of-speech and this can be directed by the other two derivatives. At the same time, the grammar orients influences the weights of associative indices and/or contextual ratios. Clearly, the mechanics for evaluation in any composition scenario are variable and completely dynamic. The execution of the derivatives could yield multiple permutations whereby some permutations may collapse while others may contribute further in the determination of the validity of the composition instance. From this, the non-collapsed permutations will be prioritized over the collapsed ones, thereby yielding valid weighing schemes at this stage.

From the remaining permutations, the prioritization could be measured by the continuity, size and length of the candidates. This stage is another tier regarding the various weighing schemes involved.

5 The dictionaries used by the current invention provide the qualitative and/or quantitative information to build the multi-dimension vector (MDV or matrix) that is created for each composition but could also contain the entire dictionary par se. The associative indices
10 could be weighed (size) according the to distance between of any one or more data strings within this MDV, and the context ratios determine similarly alternative branches relative to other data strings within the current composition instance. These could be permutations for the
15 associative indices influenced by the context ratios. The grammar orients likewise influence which permutations are prioritized according to syntax build of current composition as well as directive of immediate or next N part-of-speech expectations and/or variances thereof. The
20 matrix evolves in real-time dynamically) accordingly building collapsible and non-collapsible permutations, which also begin to influence or direct paths (greatest effect or lineage), weighing schemes, the involved derivatives themselves as well as possibly others that
25 could be activated, and eventual suggestions pertained in the permutation and evolved lineage within the MDV.

Embodiments of the present invention will now be described, by way of example only, with reference to the following examples, in which:

30 Fig. 1 shows a conventional desk telephone or mobile telephone keypad;

Fig. 2 is a table showing key-press statistics for the creation of an example data string;

Fig. 3 shows a plan view of a mobile telephone
35 adapted to have basic physical features which facilitate

a reduction in the number of key-presses required to create a data string;

Figs. 4a-c shows examples of screen-shots of a mobile telephone employing an interface system according to an aspect of the present invention;

Figs. 5a-c show alternative example screen-shots of a mobile telephone employing an interface system according to an aspect of the present invention;

Fig. 6 shows two tables illustrating comparative statistics (i.e. conventional technology vs. interface system of present invention) relating to the number of key-presses required to create the data string of Fig. 3;

Fig. 7 shows an example screen-shot and four examples Pop-Up selection lists relating to a further optional feature of a mobile telephone employing an interface system according to an aspect of the present invention;

Fig. 8 shows an example screen-shot and six example Pop-Up selection lists relating to a yet further optional feature of a mobile telephone employing an interface system according to an aspect of the present invention;

Fig. 9 shows forty-four example screen-shots relating to each key-press necessary to create the data string exemplified in Fig. 6;

Fig. 10 shows a series of example Pop-Up selection lists relating to each of the twelve conventional keypad keys of a mobile telephone employing an interface system according to an aspect of the present invention;

Fig. 11 shows an example table of associatively mapped and prioritised data strings; and

Fig. 12 illustrates the chaining of data dictionaries and associative mapping.

A basic mobile telephone keypad or QWERTY accessory keyboard can include further keys that permit a direct reduction in a user's physical interactivity with the

device using the fundamentals of etymology and ontology. These additional keys provide a means to input diverse patterns based on language or graphics and represent particular lexical fragments or basic components of such languages or graphic systems. Foldable accessory keyboards can be extended to have integrated keys dedicated to statistically extrapolated digraphs, tri-graphs, tetra-graphs etc. of any given language to make creation of words more efficient and less user-interactive. This physical interactivity reduction system (PIRS) is an example of a hardware component of the first aspect of the present invention.

Core lexical components or data string fragments combine to create larger data strings. The phrase "data string" and "character string" are interchangeable throughout the specification unless the context requires otherwise. For any given language, its core lexical components (letters, numbers and symbols) and its most occurring character string fragments can be used to create larger complete character strings that become contextual by representing meaningful words, phrases, sentences, paragraphs and fuller texts. Such patterns can include the most frequently occurring digraphs (two-letter combinations forming a single lexical unit, e.g. TH, ER, EN, AN etc.), tri-graphs (three-letter combinations forming a single lexical unit, e.g. ENT, LLY, TCH, ATE etc.), tetra-graphs (four or more letter combinations forming a single lexical unit, e.g. TIVE, ALLY, MENT, ENCE etc.) and sym-graphs (emoticons, e.g. :-) for smiley etc.). A single character being herein referred to as a "graph" and any multiple characters being herein referred to as a multi-graph. The same principles apply to graphic systems by using common and simpler abstract patterns to generate larger, more complex graphic patterns. Those fundamental components

occurring with the most frequency in any given language are most useful as key legends or indicia.

The lower the length or size of these core lexical components, the greater their simplicity and the more amplified their cognitive coherence. Cognitive coherence measures a character string's diversity, versatility and breadth of contextualisation in terms of reusability and/or its ability to build larger character strings easily and repeatedly. Letters, numbers and symbols have the highest cognitive coherence since they represent the basic lexical/numerical components and building blocks for any given language. Words, phrases, sentences and fuller texts have lower cognitive coherences the higher one goes up this chain. Digraphs have a particularly high cognitive coherence since they are practically at the bottom of the chain, having a similar cognitive coherence to that of letters. Digraphs can be loosely coupled with other letters and patterns to create larger more meaningful character strings, semantics and contexts.

The use of digraphs, tri-graphs and tetra-graphs provide easy acclimatisation toward their use because of their high cognitive coherences; i.e. they are easily recognisable and easy to place within larger patterns during the construction of meaningful words, phrases, sentences and fuller texts within any context or semantics. Digraphs, tri-graphs and tetra-graphs also reduce the amount of physical interactivity by facilitating a reduction in the number of key presses required to create a character string. This may be achieved by eliminating key-presses by means of providing data input keys having multi-character indicia which correspond with a statistical extrapolation of the most used alphanumerical character combinations (i.e. letters, numbers and symbols) in a given language. The mobile

telephone data input apparatus shown in Fig. 3 has conventional data input keys; however, it will be appreciated that keys having statistically derived multi-character indicia could alternatively be used.

5 Advantages of the mobile telephone data input apparatus of the present invention include ease of use, reduced user-interactivity, elevated efficiency and thus enhanced productivity that in turn yields improved accuracy and flexibility. Reduced interactivity is a
10 stress/strain antidote that reduces the risk and occurrence of Repetitive Strain Injuries (RSI). Furthermore, reduced interactivity has the further benefit of lessening wear and tear of the mobile telephone data input apparatus itself.

15 Comfort is a palliative benefit. The only effective way to improve ergonomics and prevent injury is to do less of any activity, e.g. reduce typing on keyboards and keypads.

The mobile telephone data input apparatus of the
20 present invention improves the overall user experience and interactivity with MT devices. The apparatus can be used independently of the mobile telephone interface system that forms a second aspect of the present invention (described in detail below), or for maximum
25 benefit, both the data input apparatus and the interface system may be used in combination.

As suggested above, a software-based approach can be used (either in isolation or in combination with the data input apparatus or hardware described above) to
30 reduce a user's physical interactivity with a mobile telephone device. This is achieved by means of a mobile telephone interface system (which will be known under the Trade Marks MT-iDICT™ and/or AdapTex™) that provides and maintains an Adaptive Intelligence™ data dictionary
35 system. This mobile telephone interface system controls

and uses various interactivity dynamics, statistics and meta-data pertaining to each entry (including but not limited to mnemonics, abbreviations or acronyms) stored within one or more data dictionaries installed within a storage means of the AdapTex™ mobile telephone interface system. Zero, one or more dictionaries may be installed at any given time. Dictionary installation and configuration thereof can be done in real-time.

Each data dictionary holds qualitative and/or quantitative information relating to a given data string. Examples of qualitative and/or quantitative information are as follows: (i) statistical information relating to a data string's historical usage or selection (i.e. frequency of use/selection, character length, lexical pattern density/versatility, chronological weight and direction/operational indicators etc.); (ii) probability information relating to a data string's historical usage (i.e. occurrence and/or association ratios of two or more sub-data strings within a longer data string; context ratios determining the likelihood of a given data string being grouped with one or more other sub-data strings to determine the context of a longer data string; or other statistical derivatives based on language and user traits such as timestamp, cognitive coherence, perceptual indices, associative indices, grammar orients, correlative weights, inference ratios and pattern factorisation etc.); (iii) run-time analytics (scaling patterns of use, historical usages, contextualization, relative associations and occurrences thereof); (iv) dictionary priority; (v) dictionary chains (where each chain also retains and uses the information in (i), (ii) and (iii) above); (vi) data string maps between other data strings (where each map also retains and uses the information in (i), (ii) and (iii) above); and (vii) translations.

Derivatives are behavioural language properties that can be rules, states, continuous or discrete values, indicators or placements at any one time, whereby each derivative condition can be dynamically manipulated

5 according to other respective derivatives. Therefore, there could be multiple ways to realise these derivatives within the interface system. Different apparatus or method or algorithm can be constructed to exploit these derivatives to provide apposite projections; for example

10 one being simple continuous or discrete statistics based systems only. The value of using these derivatives is that they permit dynamic determination of contextual, grammatical and semantic language compositions as naturally as possible.

15 The following parameters or derivatives are used in the present invention:

"**timestamp**" - the date and time the dictionary entry, chain or map was created, last used or accessed. Preferably adjacent to type of application the invention

20 is being used in conjunction with.

"**cognitive coherence**" - measures the versatility & flexibility of patterns (i.e., ease of re-usability and placement of language based patterns).

"**perceptual indices**" - measures the strength of

25 recognizing patterns (i.e., ability to deciphering language based patterns - even when patterns are incorrect / misspelled).

"**associative indices**" - measures the relevance of two or more patterns (e.g., the combination of words or the

30 appropriateness between words).

"**grammar orients**" - the lexical syntax or placement of patterns according to their semantics (i.e., rules for contextual and semantic positioning of nouns, verbs, adverbs, adjectives etc.).

"correlative weights" - measures the semantic relevance between two or more patterns (i.e., where different words mean the same or elaborate other words - much like thesaurus weights).

- 5 **"inference ratios"** - measures the likelihood of a semantic relevance between two or more patterns (i.e. occurrence of one word within other words meaning / description).

- "pattern factorisation"** - measures the ability to
10 create/breakdown larger patterns from/to smaller patterns (i.e., textual or graphic - contextually letters, numbers & symbols have highest factorization, then digraphs, tri-graphs, tetra-graphs, words, phrases, sentences, paragraphs, chapters, and finally whole texts in this
15 order of factorization).

- These and other qualitative and quantitative information are dynamically updated in real-time and in accordance of use for all entries or data strings, maps and chains, translations maintained within the
20 dictionaries (described in further detail below), and further statistical attributes & software control dynamics.

- The data dictionaries can be manually populated and/or manipulated. Alternatively, the data dictionaries
25 can or automatically populated by use of document or text scanners, which scan data strings and assemble their statistics, probabilities, run-time analytics as well as associative maps between data strings. The idea being, that such documents or texts, written by a user, reflect
30 the behavioural use of vocabulary and patterns of the language(s) reflected by the user.

- A data string may be in the form of a full data string (i.e. a word, phrase, sentence etc.) or a corresponding truncated data string such as a mnemonic,
35 abbreviation or acronym. The prioritisation of data

retrieved from a data dictionary is user-configurable to allow a user to prioritise the ordering of data listed on a display means according to selected qualitative and/or quantitative characteristics. The user configurable parameters include system behavioural parameters, data string statistics, probabilities and analytics (scaling patterns of use: historical usages, contextualization, associations and occurrences thereof), and dictionary priorities.

- 10 In addition to those mentioned above, further qualitative and/or quantitative characteristics may include:
- (i) the presence or absence of one or more data string fragments in the form of digraphs and/or tri-graphs
 - 15 and/or tetra-graphs etc within a full or truncated data string;
 - (ii) the presence or absence of truncated data strings in the form of mnemonics, abbreviations or acronyms which correspond with the full data string;
 - 20 (iii) two-way translations between full data strings and their corresponding truncated data strings;
 - (iv) the frequency of two-way verbatim, correlated and/or inferred translations between two languages (i.e. English to French);
 - 25 (v) the character-length of each full data string or its translation or any corresponding truncated data string;
 - (vi) the frequency of selection by a user of each full data string (i.e. words, numbers, symbols, emoticons etc.) or its translation or any corresponding truncated
 - 30 data string;
 - (vii) the frequency of forward and backward translations between full and truncated data strings; and
 - (viii) the frequency of forward and backward verbatim, correlated and/or inferred translations between two
 - 35 languages.

Each data dictionary may also hold indicator flags that dictate and delimit control and use of the stored data by the software, and the level that it pertains to relative software tiers.

Data strings stored within the data dictionaries are selected/accessed using the first character of the data string, and could be ordered by descending frequency and ascending length for basic default sequencing. The ordering could be configurable by the user using any field (qualitative or quantitative) of the data dictionary. Ordering can also be configured to be ascending or descending. The first character could be sourced from a single key event (e.g. Key '2' will use letter A to select all data strings which begin with that letter) or a group of first characters obtained from specific key events (e.g. Key '2' will use letters A, B, C and 2 to select all data strings that begin with the respective letters or number).

A configuration tool permits setting the various behavioural aspects (also known as physical interactivity reduction characteristics) of the AdapTex™ mobile telephone interface system. The behavioural aspects (physical interactivity reduction characteristics) are as follows but not limited to:

- (i) automatically entering a space after a selected full or truncated data string;
- (ii) limitation of displayed mnemonics to those having a total number of characters greater than the number of key presses required to display said mnemonic on the data display means;
- (iii) automatically performing forward or backward translations between mnemonics or abbreviations or acronyms and their corresponding full data strings;

(iv) prioritisation of data strings created by any given data input key having multi-character indicia, said prioritisation being based on selected qualitative and/or quantitative information relating to an initial character
5 which matches only one of the indicia on the data input key; and

(v) prioritisation of data strings created by any given data input key having multi-character indicia, said prioritisation being based on selected qualitative and/or
10 quantitative information relating to an initial character which matches any of the indicia on the data input key.

Further behavioural aspects include specifying the number of selected entries to be displayed or listed on the display means at any one time, maximising a mnemonic
15 to become the most frequent of its category with highest priority, editing of entries, or ordering run-time selections based on certain qualitative or quantitative characteristics in ascending or descending order etc.

Further behavioural aspects include specifying a
20 projection of N words or sentences by way of using the associative maps and other qualitative/quantitative statistical derivatives.

The interface system can also determine a user's most frequently used phrases (i.e. full data strings) and
25 automatically abbreviate or implode them into a mnemonic, acronym or other abbreviation (i.e. a truncated data string). This allows a user to have fewer key presses via the truncated data string which can then be manually or auto-translated into its corresponding full data
30 string. See the Trans+ and Trans- screen options or buttons on the mobile telephone of Fig. 3 which can be used to perform manual imploding or exploding of data strings. The mobile telephone can also be configured to perform this function automatically.

Due to screen size, a limited number of most used entries pertaining to a key-press can be displayed at any one time. All additional following entries that could not be displayed can be scrolled through using the navigation up to a maximum set by the configuration tool.

The diversity of dictionary types is enormous, e.g. one thousand most used words, mnemonics, acronyms, abbreviations, conversions, Short Message Service (SMS) texting data, emoticons or other data specific to the user and/or a user's working environment etc. Data dictionaries can be even more specialised by being departmentalised within specific working environments. For example, in a medical environment the dictionaries can reflect symptoms and remedies, ailments and pharmaceuticals, or simply provide normal medical terms and their definitions. In a reservation environment, the dictionaries can reflect airlines, destinations, flight codes, seating, hotels, prices etc. In an investment trading environment the dictionaries can reflect trading instruments, traders, portfolios, Reuters Instrument Codes (RIC), trader specific RICs, quantities, buy/sell prices and forecast analytics etc.

Dictionaries can also be integrated into any other software and controlled dynamically to reflect changing circumstances to the entries within respective dictionaries. This provides real-time Adaptive Intelligence relative to the user, working environment and type of system being used adjacent to its purpose.

The real-time maintenance of dictionaries and the dynamics of the AdapTex™ mobile telephone interface system allow it to contour towards a user's traits and uses of the mobile telephone, along with the user's use of language and level of vocabulary. This enables the AdapTex™ mobile telephone interface system to be adaptive and intelligent relative to the user's volume,

level and type of use of the system. Over time, the data dictionaries will evolve to reflect the most favourable and most appropriate or relevant mnemonics (truncated data strings) used by the user and thus adapt and contour the AdapTex™ mobile telephone interface system relative to, and more appropriately towards, the user.

As with the mobile telephone data input apparatus of the present invention (i.e. the hardware-based solution of the first aspect of the invention), the benefits of the mobile telephone interface system (i.e. the software-based solution of the second aspect of the invention) include ease of use, reduced user-interactivity, elevated efficiency and thus enhanced productivity that in turn yields improved accuracy and flexibility. Reduced interactivity is a stress/strain antidote that reduces the risk and occurrence of Repetitive Strain Injuries (RSI). Furthermore, reduced interactivity has the further benefit of lessening wear and tear of the mobile telephone data input apparatus itself.

Synchronisation of users' data dictionaries between mobile phones maintains accurate translations, semantics and meanings. Synchronisation can occur or be accomplished using infrared, Bluetooth® or other wireless connectivity methods available on mobile telephone devices, or can be achieved by a simple telephone call between the devices. Alternatively, central repositories or databases can be maintained by the communications service providers that the devices can access easily, or they can be maintained and accessed/downloaded via the internet. These synchronisation mechanisms maintain consistency of the dictionaries and their use thereof by groups of users. The central repositories (i.e. internet databases) provide a means to standardise dictionaries for the general population of users.

The mobile telephone interface system software further and more dramatically improves the overall user experience and interactivity with MT devices. The software elements of the mobile telephone interface system can be used independent of the hardware element of the invention described above, or it can be used complimentary to the hardware element. The combination of both the hardware and software elements of the present invention provides the greatest benefits in terms of facilitating a reduction in the number of key-presses required to create a given data string.

One means to make SMS Texting dictionaries or any other dictionary category standard and consistent by virtue of mass volume usage is by integrating them onto the devices themselves. This is something that mobile telephone manufacturers can do or facilitate quite easily. Fig. 3 shows an example of a mobile telephone adapted to have basic physical features which facilitate a reduction in the number of key-presses required to create a given data string. The mobile telephone interface system software works using the dynamic AdapTex™ data dictionaries described above that can be downloaded into the device by Internet, PC or other compatible device using cable or wireless technologies to instigate connectivity and transfer of dictionary data.

Once the mobile telephone interface system software and AdapTex™ data dictionary facilities are integrated or installed into a mobile telephone, the software aspects can use and process AdapTex™ data dictionaries using standard systemic logic to achieve optimum utilisation, i.e. using best processing methods and techniques to obtain all the efficiency benefits. The configuration tool also permits the scanning of existing messages resident on the mobile telephone or remotely mapped to the device in order to acclimatise the

AdapTex™ data dictionaries relative to the mnemonics used within the messages.

The mobile telephone interface system software uses the AdapTex™ data dictionaries according to the key sequences being used by the user either in passive mode or in active real-time mode. Various navigation features can be used in parallel or adjacent to the mobile telephone interface system software in order to access more rapidly the most frequently used/typed data strings. Thus effectively reducing the physical aspects of repetitive and recursive keying thereby enhancing efficiency and ease, and thereby improving the overall effectiveness and experience in using the mobile telephone device.

The AdapTex™ mobile telephone interface system automatically activates whenever the device enters into a state that requires any form of input, e.g. numerical or text. The activation summons a Pop-Up Selection List (PSL) according to and relative to key presses, composite key presses, or combinations thereof. The order that letters, symbols and numbers appear for selection, whether on the PSL or touch-screen implemented keypad, depends on whether the AdapTex™ mobile telephone interface system is placed in 'static mode' or 'dynamic mode'.

Static mode uses the same layout and sequence order of letters, numbers and symbols per key as set out on conventional MT devices as illustrated in Figures 4a-c. For instance, in static mode the key '2' accesses letters A, B and C and number 2 in this respective sequence/order every time key '2' is used (Fig. 4a). Alternatively, the composite 'Best Use' and Key '2' (Fig. 4b) results the same as if the device was in Dynamic Mode (described in detail below). Alternatively, the sequence 'Best Use' then Key 2 (Fig. 4c) yields a PSL with all the most used

words for every letter and number associated with Key '2', in order of frequency and length dependent on configuration settings.

- Dynamic mode allows the sequences of letters, numbers and symbols per key to reorder in real-time according to the prioritisation of the qualitative and/or quantitative information stored for each data string used by the user. Examples of qualitative and/or quantitative information are as follows:
- 10 (i) statistical information relating to a data string's historical usage or selection (i.e. frequency of use/selection, character length, lexical pattern density/versatility, chronological weight and direction/operational indicators etc.);
 - 15 (ii) probability information relating to a data string's historical usage (i.e. occurrence and/or association ratios of two or more sub-data strings within a longer data string; context ratios determining the likelihood of a given data string being grouped with one or more other
20 sub-data strings to determine the context of a longer data string; or other statistical derivatives based on language and user traits such as timestamp, cognitive coherence, perceptual indices, associative indices, grammar orients, correlative weights, inference ratios
25 and pattern factorisation etc.);
 - (iii) run-time analytics (scaling patterns of use, historical usages, contextualization, associations and occurrences thereof);
 - (iv) dictionary priority;
 - 30 (v) dictionary chains (where each chain also retains and uses the information in (i), (ii) and (iii) above);
 - (vi) data string maps between other data strings (where each map also retains and uses the information in (i), (ii) and (iii) above); and
 - 35 (vii) translations.

Referring now to Figs 5a-c, for instance, in dynamic mode the key '2' could, access letters and numbers in sequence/order of B, A, 2, C due to letter B or words beginning with B being of a higher priority than letter A or words beginning with A, and likewise letter A or words beginning with A being of a higher priority than number 2 or numbers beginning with 2, and so on (Fig. 5a). Alternatively, the composite 'Best Use' and Key '2' (Fig. 5b) results the same as if the device was in Static Mode (described above). Alternatively, the sequence 'Best Use' then Key '2' (Fig. 5c) yields a PSL with all the words for every letter and number associated with Key '2', in order of priority and length dependent on configuration settings.

Priority is only one example of information, parameters etc which might order the words or strings. Many others are described herein. In addition priority may be determined from any combination of parameters of a specific data string or word.

The first data string or system option in a PSL is highlighted for selection by the user by default. The highlighted data string or system option is selected/activated using the navigation system or screen option keys. Highlighted data strings or system options are also automatically selected if any other key is pressed apart from the navigation or screen option keys (i.e. see the 'Select' option in Fig. 9).

Alternatively, the first letter of each data string is underlined whereby pressing the respective key selects the data string or system option without the need to scroll to it first. Where there is more than one data string or system option with the same initial character, these are scrolled through in the order presented in the Pop-Up selection list. Similarly, data strings or system options with different initial characters but respective

to one key (e.g. 'Input Text' and 'Help' relative to the 4ghi key) are scrolled through in the order presented in the Pop-Up selection list. Selection of 'Input Text' will result in a prompt for typing of an SMS text message
5 or any other text input or conversion into text input.

With regard to the entering of a telephone number, conventionally this is done by entering the number itself or via a phonebook search. However, with regard to the present invention, as a user begins to type a number,
10 best matches of the typed digits are matched to those stored within the mobile telephone number phonebook to display a filtered Pop-Up name list relative to the digits typed and selections and prioritizations derived from the data storage (dictionary, data string, chain or
15 map etc.) qualitative and/or quantitative information, methods, and patterns of use. This facilitates a more efficient means of selection and is an example demonstrating the integration of AdapTex™ with other software such as the device phonebook system and storage.
20 Here the AdapTex™ treats other software information as any other dictionary and provides other software systems to fully utilise all of the AdapTex™ interface features.

Keypads provided on touch-screen devices can therefore also dynamically display the re-ordered
25 sequence/order of letters associated per key relative to the prioritizations derived from the data storage (dictionary, data string, chain or map etc.) qualitative and/or quantitative information, methods, and patterns of use of the associated letters or words beginning with
30 those letters for each respective key.

Additional conventional symbols, like graphic smiley faces or white characters like ENTER or RETURN can also be included to expand the range of characters available to the AdapTex™ mobile telephone interface
35 system. This also includes symbol based Emoticons (e.g.

`:-)` represents Smiley, `>r` represents 'greater' or
`@}>--` represents a 'flower'.

During PSL, the navigation system can be used to scroll through the items according to the cursor
5 direction being applied. Alternatively, repetitious pressing of the key that invoked the PSL for that key will scroll left to right through the letters and numbers associated to that key.

For instance, in the above example for both static
10 and dynamic modes of operation and PSL instigated by Key '2' and/or 'Best Use' and Key '2', repeated Key '2' or cursor left or right would scroll horizontally through each letter and number, whereby a cursor up or down would scroll vertically through each letter's or number's
15 listed most used mnemonics, and whereby cursor trigger-down, cursor right or left, the activating key, a timeout, or any other key press would select the current highlighted entry. Alternatively, in the above example for both static and dynamic modes of operation and PSL
20 instigated by 'Best Use' then Key '2', repeated Key '2' or cursor up or down would scroll vertically through each PSL entry, whereby cursor trigger-down, cursor right or left, the activating key, a timeout, or any other key press would select the current highlighted entry.

25 To type the following SMS text message "Dear Friend, Please call me as soon as possible to fix a date for another meeting" requires the following events/key presses under the AdapTex™ mobile telephone interface system based upon the Mobile Phone Example Pop-Up
30 Selection Lists (see below). Automatic forward translation from mnemonic to description/translation is assumed to be set to ON via the configuration tool, as is auto-spacing after selecting a mnemonic. Upper casing of letters (Key '*' x3=3), general punctuation (Key '1'x2=2)
35 and spacing between words (Auto-Spacing ON=0) account for

+5 additional key presses in the example shown in the table in Fig. 6.

Fig. 9 shows example screen-shots of each key-press necessary to create the data string exemplified in Fig.

5 6. In these examples, the optional physical interactivity reduction functions 'Auto Spacing' and 'Auto-Translate' are active and the 'Auto-project' (described below) is OFF. Note that the 'Auto-Translate' function can alternatively be performed manually by
10 pressing the 'Trans+' key shown in Fig. 3. The software option changes from 'More' to 'Select' when the Pop-Up selection (PSL) mode is active. 'Select' allows an item to be selected from the PSL whilst retaining the current PSL active. For example, if 'Select' is used in screen
15 event 3 shown in Fig. 9, then the data string "date" would be chosen (i.e. the full data string of its corresponding truncated data string - "D8") and the PSL will remain active for key 'D' and retain the PSL on its first index, i.e. 'D'. However, using the same example,
20 if data string selection is achieved by means of a 'Joystick Left' action, the data string "date" would be chosen and the PSL will remain active for key 'D' and retain the PSL on the current index, i.e. 'D'. Further key presses of the current active key, e.g. key- 3-DEF,
25 would move to the next character selection of the same key, i.e. key 'E' and display it's PSL.

If the 'Auto-project' mode was set to ON in the example above, then a projection of n words of the entire phrase would be projected upon keying 'd' and
30 automatically or manually selecting 'Dear'.

The AdapTex™ mobile telephone interface system is not a Predictive Typing System (PTS). PTS integration with the AdapTex™ mobile telephone interface system would allow the PTS to predict more accurately since it
35 is adapting to the users vocabulary in real-time and can

presume to hit the users most used data strings (i.e. words, mnemonics etc.) at every instance.

The AdapTex™ mobile telephone interface system formulates logic and prioritisations derived from the data storage (dictionary, data string, chain or map etc.) qualitative and/or quantitative information, methods, frequencies and patterns of behaviour and usages of words/mnemonics of the user. Thus, it becomes adaptive to the user and the user's vocabulary and traits. This provides the most favourable and most appropriate or relevant choices for the user based on the user's actual vocabulary, historic usages, methods and prioritizations derived from the data storage (dictionary, data string, chain or map etc.) qualitative and/or quantitative information, and patterns of use thereof. The AdapTex™ mobile telephone interface system provides mnemonic choices based on usages rather than guesswork to what the user is trying to type relative to a static generic dictionary.

20 An extension to the translation mode is the automatic generation of acronyms, abbreviation and conversions. Here the interface system can dynamically determine acronyms, abbreviations and conversions for such mapped associations, thereby providing automated translator shortcuts for the most recurring or commonly used phrases, sentences or texts of n character strings, which can be stored and maintained within any dictionary and made readily available. The user is made aware of such automated acronyms, abbreviations and conversions via the interface system dictionary console, display / reporting and edit features where the user can also create personalized shortcuts and where these shortcuts can also include system or device commands and executable instructions / macros.

The mobile telephone interface system is also provided with a 'mapping mode'. Dependent on this mode being activated and various chains between dictionaries being predefined and established by the user during
5 installation or via run-time configuration tools, or automatic chaining is activated, the interface system will perform chained translations of typed or highlighted text. This involves the interface system scanning and mapping appropriate translations from one dictionary to
10 another. Here the interface system maintains lookup chains between any dictionaries such that dynamic mapping can be made from one dictionary to another, and so on. For example, English-to-French (dog, chien) and French-to-German (chien, hund) dictionaries can be chained such
15 that it can infer English-to-German (dog, hund) mapping.

More sophisticated dynamic mappings could chain for example a symptoms dictionary to a prescriptions dictionary whereby relevant character strings are matched between any dictionary entries and translations to
20 dynamically chain such dictionaries together and induce n ailment to medicine mappings. A single mapping is definitive whereas a list of n mappings are prioritised accordingly and made available via the PSL feature. The number of chained dictionaries is dependent on the number
25 and permutations of installed dictionaries.

The mobile telephone interface system is also provided with a 'project mode'. When activated, the various maps between entries within respective installed dictionaries (the maps being predefined or established
30 automatically or manually by the user during installation or run-time) allow the interface system to determine and project the most likely associations between n entries relative to the keyed or highlighted text. The most relevant, user contoured and adaptive appropriations

spanning n derived sub-data strings are then displayed for selection by a user.

The interface system maintains associative maps between data strings within two or more dictionaries, such that these maps can be used to dynamically infer associations between data strings based on map statistics, probabilities and analytics (scaling patterns of use: historical usages, contextualization, associations and occurrences thereof). This allows the interface system to project and retrieve the n most likely appropriations or closely associated data strings from the dictionaries that are relevant, definitive and user oriented, and each data string being apposite to context.

Optionally, the data processing means can dynamically retrieve a list of alternative appropriations with respect to each mapped association used to induce each of the n respective data strings, whereby each list of alternative appropriations are prioritised and made available via the PSL feature. Once a longer data string is selected from the PSL, this dynamically induces and propagates a further projection and retrieval of n further data strings, each corresponding to a previous mapped association or PSL selection.

Fig. 11 shows a table of associatively mapped and prioritised data strings. The AdapTex™ mobile telephone interface system can multi-map dictionary entries to other entries within the same and/or other dictionaries. These maps are based on analytics of patterns of use or relativity between the mapped entries. These analytics are dynamic because they change priorities and switch context according to patterns of use.

Thus, a user can specify n projections whereby AdapTex™ will map entries to give n sequential appropriation lists of up to, say, five subsequent

outcomes relative to a previous entry. Each subsequent appropriation list is prioritized and each can then be selected out of the five if required, most likely not since the top entry for each list will be most likely for use.

For example, if the word "Next" is typed or keyed then the projected words (sub-data strings) shown in Fig. 11 would appear (i.e. 'generation', 'of', 'adaptive', 'intelligence', 'interfaces'). Each projected word produces a PSL (for example, the word 'generation' produces a list of other words below it) that can be manually toggled for selection when a user skips to each projection unless a user accepts the suggested projection. The PSL is in priority order of patterns of use and context switching. The spacing in the table is for clarity only and would not appear on as such on the display.

On a non-touch screen system the user would navigate to the appropriate word for changing and on a touch-screen simply tap the word with the stylus. In either case the PSL for that word would appear for alternative selection or replacement of the suggested word. If a suggested word is altered then the subsequent words would change dynamically, contextually as well as associatively map to the new selected word. The user can alternatively type a new word from scratch over any original word selection.

On typing each letter of the word 'Next', appropriate selection lists are derived where the beginning of each list entry reflect the current typed letters. For example, typing the letters 'Ne' would provide a list of say, 'Next, Never, Neither, Neighbour, Nederland'. From such a list the highest weighted entry would be shown, in this particular example 'Next' and the

letters 'xt' would be highlighted and available for selection to complete word 'Next'.

AdapTex™ will also appropriate the word as it is typed and dynamically change the projections according to any changes to it. This makes it much more Adaptive Intelligent than it already is. An option to highlight only words within a projection that require changing is provided, where remaining unselected words are not dynamically changeable.

10 The interface system could exploit the flexibility in its structure to provide projections based on true syntax, context, semantic and grammar meta data.

Continual flow from one selection to subsequent words could be provided such that a SPACE or cursor movement is adequate to perform a selection and move to word relative to direction without the need to use additional select methods, i.e. a cursor movement from a highlight auto-selects the highlighted item unless another mechanism is used to do otherwise.

20 The data processing means can provide manual or automatic spell check features. The data processing means can provide a freeze point enabling the retrieval of static constant appropriations as opposed to dynamic, and which can be based on either most recent or current captured entry statistics, probabilities and analytics (scaling patterns of use: historical usages, contextualization, associations and occurrences thereof), or manually intervened prioritization or overrides". The data processing means can operate on any type of interface medium, keyboard and/or keypad, whether they are conventional or alternative.

Duplications are handled by prioritising the installed dictionaries whereby entries within a higher priority dictionary have precedence or are determined if

manual overrides have been put in place by the user during installation or run-time configuration.

The following provides an example method to represent dictionary information, indexing and chaining as shown in Fig. 12. It also depicts an example method to represent dictionary entry information, indexing and mapping. Although RDBMS could be used, a dynamic method could use system character code tables or repertoires that come in standard ASCII, ISO, UNICODE and other formats that also include language character variants. The system character codes provide the index to each series of dictionary entries that begin with that code. Subsequent entries of the same code are dynamically generated and mapped to the previous entry in the same array for that code. Each entry holds its own statistical derivatives (i.e., timestamp, translation, expansion, frequency, length, cognitive coherence, perceptual indices, associative indices, grammar orient, correlative weights, inference ratios, pattern factorization and context probabilities etc.).

Additionally entry maps are formed to associate entries between themselves, i.e. maintain etymological relationships and statistical derivatives between entries. These entry maps again are indexed using system character code tables. The system character codes provide the index to each series of entry maps that begin with that code. Subsequent maps of the same code are dynamically generated and mapped to the previous map in the same series of that code.

Dictionary chaining provides correlation and inference between dictionaries and their entries and maps. Entry mapping provides inference and association between entries and their maps.

This method allows dynamic generation of dictionaries and their variable entries and respective

entry maps. It also provides an example indexing system for rapid access to entries and their associated or related map entries. The method permits a spatial/multi-dimensional matrix to represent dictionary dynamics.

5 A unique aspect of the present invention is that it provides mechanisms or Application Programming Interfaces (API) that allows other software systems to utilise and benefit from all the features of this invention, and to enable improved experiences for the user with such
10 software systems. Additional to this, the API allows other software systems data storage or information repositories to be handled by this invention in similar manner to its own dictionaries etc.

Predictive Typing Systems (PTS) do not reduce the
15 amount of interactivity as effectively as the AdapTex™ mobile telephone interface system purely because the former still requires further key-presses to guide its prediction, whereas the latter simply provides discrete choices of full or partial mnemonics (i.e.
20 shortcuts/hands, whole words, phrases, or partial patterns that can be used to build up or complete other patterns, e.g. di-graphs, tri-graphs, tetra-graphs and symbol-graphs).

The AdapTex™ mobile telephone interface system has
25 a standardised set of default dictionaries. However, other or additional dictionaries can be installed as standard either when the device is shipped or when users pre-install their bespoke dictionaries on setup. These new entries can be edited by the user at will.

30 The examples shown in Fig. 10 assume that the AdapTex™ mobile telephone interface system is in static mode, whereby the sequence/order of displayed letters associated with their respective key is depicted in conventional chronological order. Whenever in text input
35 mode the illustrated Pop-Up selection lists are displayed

according to the activating key and appropriate navigations. The Pop-Up selection lists also depict examples of the most frequently used mnemonics based on prioritizations derived from the data storage

- 5 (dictionary, data string, chain or map etc.) qualitative and/or quantitative information, methods, and patterns of use or numbers relative to each letter or digit associated with its respective key.

The Pop-Up selection lists illustrated in Fig. 10
10 are merely examples and would otherwise dynamically depict entries within the installed dictionaries and ordered relative to each user's patterns of use. Keys '*' and '#' also provide emoticons as well as normal functions. Pop-Up selection lists can also provide for
15 system options. For example, Keying 'S' may, in addition to displaying a filtered and prioritised list of data strings beginning with the letter 'S', also display system options such as 'send' or 'spell check'.

The 'Best Use' then 'Key' combination creates a
20 composite mnemonic list by taking the first/priority mnemonic for each corresponding letter or number and combining it to make an optimal list. This is relative to static and dynamic modes of operations as earlier exemplifications show, i.e. presented in order of the
25 letters and numbers shown and dependent on mode of operation when PSL is instigated. For instance, using the PSL examples above and in static mode 'Best Use' then Key '4' will give G2g, H2O, Ic, 4get, whereas in dynamic mode it may possibly give 4get, H2O, G2g, Ic dependent on
30 which start letter, number or mnemonic is most used.

User typed words are entered into the AdapTex™ mobile telephone interface system's data dictionary when no such entry existed beforehand. In addition, relevant data string maps, associations and contextualization
35 parameters are also derived and maintained for all such

new data string entries within the data storage means. This mechanism allows the device to adapt to the users usage and environment that dictates type and level of use. The new entries are immediately accessible by
5 normal AdapTex™ means. Thus, the PIRS and/or AdapTex™ mobile telephone interface system adapt in real-time making interaction for the user more familiar and relative information more apparent to use and/or access.

Software application names relative to a letter on
10 a key can be set to macro mode, thus when pressing the key the PSL gives option to start an application from its list (e.g., Key '9': WORD, XCEL, YAHOO, ZANY KONG).

Symbols can be accessed using the software 'Symbols' option. The symbols are categorised and
15 ordered according to qualitative and/or quantitative priority. The priority determines the ease of access to the symbols when the 'Symbols' option is instigated. The example illustrated in Fig. 7 depicts the PSL for the Symbol option along with example categories. Normal
20 navigation system usages apply access to the various symbols.

Software facilities, inserts or application macros can be accessed using the software 'More' option. Again, like 'Symbols', the 'More' options are categorised and
25 ordered according to qualitative and/or quantitative priority. The priority determines the ease of access to the options when 'More' is instigated. The example illustrated in Fig. 8 depicts the PSL for the 'More' option along with example categories. Normal navigation
30 system usages apply access to the various 'More' options. Optionally, one or more mobile telephone interface systems can be used as an input medium for other technologies by way of wired or wireless communications (i.e. infrared or Bluetooth® etc.). For example, one or
35 more of these systems can remotely be used as the

keyboard for a PC by replacing the conventional PC
keyboard. The dictionary synchronisation modules between
the personal computing device and the PC can also control
and relay data strings from the device to the PC as a
5 default input medium for the PC, as well as synchronise
dictionaries simultaneously.

The invention provides a mobile telephone data
input apparatus comprising a plurality of data input keys
having multi-character indicia, said apparatus adapted to
10 facilitate a reduction in the number of key presses
required to create a given data string to less than the
number of characters within said data string.

The multi-character indicia are selected to accord
with a statistical extrapolation of the most used
15 alphanumerical character combinations in a given
language.

The inventions provides a mobile telephone
interface system adapted to facilitate a reduction in the
number of data input key presses required to create a
20 data string to less than the number of characters within
said data string; said system comprising mobile telephone
data input apparatus; data storage means; data processing
means; and data display means, wherein the data
processing means: filters data stored within the data
25 storage means by initial character, as determined by the
character or characters ascribed to a data input key
initially pressed by a user; prioritises said filtered
data in real-time according to user-configurable
prioritisation parameters; and displays one or more
30 prioritised data strings on the data display means for
subsequent selection by the user.

A plurality of the most relevant longer data
strings may be displayed in a prioritised list for
selection by a user. Selection of a longer data string or
35 part of a longer data string induces a repetition of

associative mapping such that a further one or more relevant longer data strings are displayed for selection by a user. The relevance or the prioritisation of each longer data string is determined according to statistical and/or probability information stored within the data dictionaries.

Statistical information relates to but is not limited to the historical inputting and/or selection of data strings. The historical inputting and/or selection information can be one or more of the following: (i) frequency of use; (ii) frequency of selection (iii) character length; (iv) lexical pattern density; and (v) chronological weighting.

Probability information can be one or more of the following: (i) occurrence and/or association ratios of two or more sub-data strings within a longer data string; (ii) context ratios determining the likelihood of a given data string being grouped with one or more other sub-data strings to determine the context of a longer data string. The data processing means can selectively bypass or reset the dynamically updated qualitative and quantitative information.

Synchronisation of data dictionaries between two or more mobile telephones can be accomplished by means of wireless connectivity. Synchronisation of data dictionaries between two or more mobile telephones can be accomplished by means of data exchange during a standard telephone call. Synchronisation of data dictionaries between two or more mobile telephones can be accomplished by means of downloading from a common database.

The dictionaries may be manually populated and/or manipulated. The population of each data dictionary with data and its corresponding qualitative and/or quantitative information may be accelerated by uploading onto the data storage means data strings resident on a

mobile telephone or a remotely connected device.

Alternatively, the dictionaries are populated by scanning external data strings by means of scanning apparatus.

- The configuration means is adapted to allow a user
- 5 to selectively enable or disable physical interactivity reduction characteristics of the interface system which facilitate a reduction in the number of key presses required to create a data string. The physical interactivity reduction characteristics are selected from
- 10 the group comprising but not limited to:
- (i) automatically entering a space after a selected data string;
 - (ii) limitation of displayed mnemonics to those having a total number of characters greater than the number
 - 15 of key presses required to display said mnemonic on the data display means;
 - (iii) automatically performing forward or backward translations between mnemonics or abbreviations or acronyms and their corresponding full data strings;
 - 20 (iv) prioritisation of data strings created by any given data input key having multi-character indicia, said prioritisation being based on selected qualitative and/or quantitative information relating to an initial character which matches only one of the
 - 25 indicia on the data input key; and
 - (v) prioritisation of data strings created by any given data input key having multi-character indicia, said prioritisation being based on selected qualitative and/or quantitative information relating to an
 - 30 initial character, which matches any of the indicia on the data, input key.

Successive key presses or composite key presses act to filter further the number of data strings displayed on the data display means for subsequent selection by the

35 user. The one or more data strings displayed on the data

42

display means for subsequent selection by the user are displayed in list format in descending order of priority.

Modifications and improvements may be made without departing from the scope of the present invention.

5

10

15

20

25

30

35

CLAIMS

1. A method of character recognition for a mobile telephone data input apparatus comprising a plurality of data input keys having multi-character indicia, said method adapted to facilitate a reduction in the number of user interactions required to create a given data string to less than the number of characters within said data string, the method comprising the following steps:
 - a. storing a set of data strings each with a priority indicator associated therewith, wherein the indicator is a measure of a plurality of derivatives associated with the data string;
 - b. recognising an event;
 - c. looking up the most likely subsequent data string to follow the event from the set of data strings based on one or more of the plurality of derivatives;
 - d. ordering the data strings for display based on the priority indicator of that data string;
 - e. if the required subsequent data string is included in the list selecting the required subsequent data string;
 - f. if the required subsequent data string is not included in the list entering a event and repeating steps b to e;
 - g. updating the priority indicator of the selected data string;
 - h. updating the set of data strings based on the updated priority indicator.
2. The method of claim 1, further comprising providing the derivatives as a plurality of etymological and ontological derivatives.
3. The method of claim 1 or claim 2, further comprising providing the derivatives to include one or more of a timestamp, a cognitive coherence, a perceptual index, an

associative index, a grammar orient, a correlative weight, an inference ratio and a pattern factorisation.

4. The method of any one of claims 1 to 3, further comprising determining the priority indicator from
- 5 qualitative and quantitative data related to each data string in the set.
5. The method of any one of claims 1 to 4, further comprising determining the priority indicator from one or more of the following:
 - 10 a. statistical information;
 - b. probability information;
 - c. data string analysis information;
 - d. dictionary priority;
 - e. dictionary chains;
 - 15 f. data string maps between other data strings; and
 - g. data string translations.
6. The method of any preceding claim, wherein the step of recognising an event comprises recognising one or
- 20 more of a character, a graph, a multi-graph, a data string, a context, a symbol or any other user or machine generated input.
7. The method of any preceding claim, further comprising providing the data set as a dictionary including a plurality of words, phrases and any other
- 25 data string which might be used in the communication of a message.
8. The method of claim 7, further comprising adding data strings to the dictionary as they are entered by a user.
- 30 9. The method of any preceding claim, further comprising updating all priority indicators dynamically in real-time.
10. The method of any preceding claim, further comprising maintaining lookup maps between two or more
- 35 data dictionaries such that a given data string in a

first data dictionary is mapped to a data string or strings in one or more other data dictionaries for selection by a user.

- 5 11. The method of claim 10, further comprising ordering a data string in a first data dictionary that is mapped to a plurality of data strings in one or more other data dictionaries based on the priority indicator to enable selection by a user.
- 10 12. The method of any preceding claim, further comprising displaying a list of the most likely subsequent data string in an order based on the priority indicator to enable the user to select the required subsequent data string.
- 15 13. A character recognition apparatus for a mobile telephone comprising a plurality of data input keys having multi-character indicia, said apparatus adapted to facilitate a reduction in the number of user interactions required to create a given data string to less than the number of characters within said data
- 20 string, the apparatus comprising:
- a. a memory for storing a set of data strings each with a priority indicator associated therewith, wherein the indicator is a measure of a plurality of derivatives associated with the data string;
 - 25 b. an event recognition module for recognising an event;
 - c. means for looking up the most likely subsequent data string to follow the event from the set of data strings based on one or more of the plurality of derivatives;
 - 30 d. display means for displaying a list the most likely subsequent data string in an order based on the priority indicator of that data string;
 - e. means for selecting the required subsequent data string if it is included in the list;
 - 35 f. data entry means for entering an event;

- g. means for updating the priority indicator of any selected data string and the set of data strings based on the updated priority indicator.
14. A character recognition apparatus according to claim 5 13, wherein the plurality of derivatives comprise a plurality of etymological and ontological derivatives.
15. A character recognition apparatus according to claim 13 or claim 14, wherein the derivatives include one or more of a timestamp, a cognitive coherence, a perceptual 10 index, an associative index, a grammar orient, a correlative weight, an inference ratio and a pattern factorisation.
16. A character recognition apparatus according to any one of claims 13 to 15, wherein the priority indicator 15 comprises qualitative and quantitative data related to each data string in the set.
17. A character recognition apparatus according to any one of claims 13 to 16, wherein the priority indicator includes one or more of the following:
- 20 a. statistical information;
b. probability information;
c. data string analysis information;
d. dictionary priority;
e. dictionary chains;
25 f. data string maps between other data strings; and
g. data string translations.
18. A character recognition apparatus according to any one of claims 13 to 17, wherein the event includes one or more of a character, a graph, a multi-graph, a data 30 string, a context, a symbol or any other user or machine generated input.
19. A character recognition apparatus according to any one of claims 13 to 18, wherein the data set is a dictionary including a plurality of words, phrases and

any other data string which might be used in the communication of a message.

20. A character recognition apparatus according to claim 19, wherein data strings are added to the dictionary as they are entered by a user.
21. A character recognition apparatus according to any one of claims 13 to 20, wherein the priority indicators are updated dynamically in real-time.
22. A character recognition apparatus according to any one of claims 13 to 21, further comprising a lookup map between two or more data dictionaries such that a given data string in a first data dictionary is mapped to a data string or strings in one or more other data dictionaries for selection by a user.
23. A character recognition apparatus according to claim 22, wherein, further comprising ordering a data string in a first data dictionary that is mapped to a plurality of data strings in one or more other data dictionaries based on the priority indicator to enable selection by a user.
24. A character recognition apparatus according to any one of claims 13 to 23, wherein the most likely subsequent data string are ordered based on the priority indicator to enable the user to select the required subsequent data string.
25. A character recognition apparatus according to any one of claims 13 to 24, further including configuration means adapted to allow a user to selectively enable or disable physical interactivity reduction characteristics of the interface system which facilitate a reduction in the number of key presses required to create a data string.
26. A character recognition apparatus according to any one of claims 13 to 25, wherein the physical

interactivity reduction characteristics are selected from the group comprising but not limited to:

- a. automatically entering a space after a selected data string;
- 5 b. limitation of displayed mnemonics to those having a total number of characters greater than the number of key presses required to display said mnemonic on the data display means;
- 10 c. automatically performing forward or backward translations between mnemonics or abbreviations or acronyms and their corresponding full data strings;
- 15 d. prioritisation of data strings created by any given data input key having multi-character indicia, said prioritisation being based on selected qualitative and/or quantitative information relating to an initial character which matches only one of the indicia on the data input key; and
- 20 e. prioritisation of data strings created by any given data input key having multi-character indicia, said prioritisation being based on selected qualitative and/or quantitative information relating to an initial character, which matches any of the indicia on the data, input key.
- 25 27.A mobile phone including a character recognition apparatus according to any of claims 12 to 26.

1 / 16

1 Mail	2 ABC	3 DEF
4 GHI	5 JKL	6 MNO
7 PQRS	8 TUV	9 WXYZ
* a/A	0 +	#

Fig. 1

Fig. 2 To type the following SMS message "Dear Friend, Please call me as soon as possible to fix a date for another meeting" requires extensive and repetitive keying as depicted below. Upper casing of letters (Key *x3=3), general punctuation (Key 1x2=2) and spacing between words (Key #x15=15) accounts for an additional +20 key presses in the example below.

[illegible]

3 / 16




Fig. 3

Mobile Phone with Basic Physical PIRS features
(PIRS & MT-iDICT Software Contained within the Device)

4 / 16

Fig. 4a

	A	B	C	2
	And			
	Asap			
	Ally			
Input Text	Another			
A: a				
Best Use	Symbol	More		

Sample Screen with PSL Activation
for Static Mode: Key 2

Fig. 4b

	B	A	2	C
	B4			
	Been			
	British			
Input Text	Balloon			
B: b / be / bee				
Best Use	Symbol	More		

Sample Screen with PSL
Activation for Static Mode:
Best Use + Key 2

Fig. 4c

	And	
	B4	
	Call	
	2nite	
Input Text	Asap	
And: and / &		
Best Use	Symbol	More

Sample Screen with PSL
Activation for Static Mode:
Best Use then Key

5 / 16

Fig. 5a

	B	A	2	C
	B4			
	Been			
	British			
Input Text	Balloon			
B: b / be / bee				
Best Use	Symbol	More		

Sample Screen with PSL
Activation for Dynamic
Mode: Key 2

Fig. 5b

	A	B	C	2
	And			
	Asap			
	Ally			
Input Text	Another			
A: a				
Best Use	Symbol	More		

Sample Screen with PSL
Activation for Dynamic Mode:
Best Use + Key 2

Fig. 5c

	B4	
	And	
	2nite	
	Call	
Input Text	Been	
B4:Before		
Best Use	Symbol	More

Sample Screen with PSL
Activation for Dynamic Mode:
Best Use then Key 2

5 / 16

Word:	Key x Presses + Cursor Movement (letter or mnemonic - translation obtained)	
Dear	3 x 1 + 2Down (Dear)	
Friend	3 x 2 + 3Down (Friend)	
Please	7 x 1 + 1Down (Pls - Please)	
call	2 x 3 + 3Down + Select (call me)	
me		
as	2Down (asap - as soon as possible)	
soon		
as		
possible		
to	2 x 3 (2 - to)	
fix	3 x 3 + 1Down (fix)	
a	2 x 1 (a)	
date	3 x 1 + 1Down (D8 - date)	
for	4 x 4 (4 - for)	
another	2 x 1 + 3Down (another)	
meeting	6 x 1 + 3Down (meeting)	
PIRS / MT-iDICT:	3+5+2+7+2+3+4+1+2+4+4+4+5=46	-i.e. summation of key presses for each word
Actual Length:	81	-i.e. actual message length
Excess Presses:	46 - 81 = -35 -i.e. 35 less key presses than actual message length (43.2% PIRS Improvement)	
Mobile Phone:	164	-i.e. number of key presses for conventional Mobile Phone
Improvement:	46 - 164 = -118 -i.e. 118 less key presses than conventional Mobile Phone (71.9% PIRS Improvement)	

Actual = 81 characters	Standard Mobile		PIRS Mobile	
	Activity	%benefit	Activity	%benefit
Key Presses	164	-202.5%	49	+60.5%
Key Presses v. Actual	+83	-102.5%	-32	+39.5%
PIRS Mobile v. Standard Mobile			-115	+70.1%

Effectiveness Comparison Standard x. PIRS Mobile

Fig. 6

7 / 16

Input Text	Send	Insert
	Text	Language
	Symbol	In Method
	Macros	Priority
	Forward	Reply
Send: this message / other item		
Best Use	Symbol	More

Other MORE Categories
by Example

Send	Message
File	Picture
Telephone	Email
Animation	Video
Sound	Melody

Insert	Emoticon
File	Picture
Telephone	Email
Animation	Video
Sound	Symbol

Text	Size
Font	C Align
L Align	R Align
Auto Align	Bold
Underline	Italic

Language	English
German	French
Std ABC	123
Spanish	Italian
Chinese	Japanese

In Method	MT-iDICT
Multi Lap	T9
Predictor	Accessory
Voice	Infra-red
Bluetooth	Keyboard

Macros	Word
Elite	Excel
Lotus	Yahoo
Z Kong	Invaders
Golf	Soccer

MORE Option / Access
Main MORE Category by Example

Fig. 8

8 / 16

		Help
		Cancel
		Best Use
		Symbols
Input Text	More Options	
Select an option or input a message		
Best Use	Symbol	More

1. System starts Text Input

		D	E	F	3
		D8			
		Dear			
		Don't			
Input Text	Did U C				
D					
D: D / d					
Best Use	Symbol	Select			

2. Key-3.DEF Pressed

		D	E	F	3
		D8			
		Dear			
		Don't			
Input Text	Did U C				
Date					
D8: date					
Best Use	Symbol	Select			

3. Joystick down 1

		D	E	F	3
		D8			
		Dear			
		Don't			
Input Text	Did U C				
Dear					
Dear					
Best Use	Symbol	Select			

4. Joystick down 1

		D	E	F	3
		End			
		Ence			
		Elly			
Input Text	Every 1				
Dear E					
E: E / e					
Best Use	Symbol	Select			

5. Key-3.DEF Pressed

		D	E	F	3
		Fix			
		For			
		Friend			
Input Text	Feel like it				
Dear F					
F: F / f					
Best Use	Symbol	Select			

6. Key-3.DEF Pressed

		D	E	F	3
		Fix			
		For			
		Friend			
Input Text	Feel like it				
Dear Fix					
Fix					
Best Use	Symbol	Select			

7. Joystick down 1

		D	E	F	3
		Fix			
		For			
		Friend			
Input Text	Feel like it				
Dear For					
For					
Best Use	Symbol	Select			

8. Joystick down 1

		D	E	F	3
		Fix			
		For			
		Friend			
Input Text	Feel like it				
Dear Friend					
Friend					
Best Use	Symbol	Select			

9. Joystick down 1

Fig. 9

9 / 16

	1	.	-	?
	10		100	
	12		One	
	150		1000	
Input Text	118		1483	
Dear Friend 1				
1: 1 / One				
Best Use	Symbol	Select		

10. Key -1:.,? pressed

	1	.	-	?
	.		-	
	Spc		Enter	
	-		:	
Input Text	-		:-	
Dear Friend,				
Punctuation: Comma				
Best Use	Symbol	Select		

11. Key -1:.,? pressed

	P	Q	R	S	7
	Pls				
	Pretend				
	Powerful				
Input Text	Present8n				
Dear Friend, P					
P: P / p / pee					
Best Use	Symbol	Select			

12. Key -7:PQRS pressed

	P	Q	R	S	7
	Pls				
	Pretend				
	Powerful				
Input Text	Present8n				
Dear Friend, Please					
Pls: Please					
Best Use	Symbol	Select			

13. Joystick down 1

	A	B	C	2
	And			
	Asap			
	Another			
Input Text	Alternative			
Dear Friend, Please a				
A: A / a				
Best Use	Symbol	Select		

14. Key -2:ABC pressed

	A	B	C	2
	B4			
	Been			
	British			
Input Text	Balloon			
Dear Friend, Please b				
B: B / b / be / bee				
Best Use	Symbol	Select		

15. Key -2:ABC pressed

	A	B	C	2
	Call			
	Cul8r			
	Call me			
Input Text	Conversation			
Dear Friend, Please c				
C: C / c / see				
Best Use	Symbol	Select		

16. Key -2:ABC pressed

	A	B	C	2
	Call			
	Cul8r			
	Call me			
Input Text	Conversation			
Dear Friend, Please call				
Call				
Best Use	Symbol	Select		

17. Joystick down 1

	A	B	C	2
	Call			
	Cul8r			
	Call me			
Input Text	Conversation			
Dear Friend, Please see you later				
Cul8r: see you later				
Best Use	Symbol	Select		

18. Joystick down 1

Fig. 9b

10 / 16

	A	B	C	2	
	Call				
	Cul8r				
	Call me				
Input Text	Conversation				
Dear Friend, Please call me					
Call me					
Best Use	Symbol	Select			

19. Joystick down 1 + Selected

	A	B	C	2	
	And				
	Asap				
	Another				
Input Text	Alternative				
Dear Friend, Please call me a					
A: A / a					
Best Use	Symbol	Select			

20. Previous Select retains current active PSL and goes to 1st index of PSL, i.e. A
NO KEYING OCCURS HERE

	A	B	C	2	
	And				
	Asap				
	Another				
Input Text	Alternative				
Dear Friend, Please call me and					
And					
Best Use	Symbol	Select			

21. Joystick down 1

	A	B	C	2	
	And				
	Asap				
	Another				
Input Text	Alternative				
Dear Friend, Please call me as soon as possible					
Asap: as soon as possible					
Best Use	Symbol	Select			

22. Joystick down 1

	A	B	C	2	
	B4				
	Been				
	British				
Input Text	Balloon				
Dear Friend, Please call me as soon as possible b					
B: B / b / be / bee					
Best Use	Symbol	Select			

23. Key -2:ABC pressed

	A	B	C	2	
	Call				
	Cal8r				
	Call me				
Input Text	Conversation				
Dear Friend, Please call me as soon as possible c					
C: C / c / see					
Best Use	Symbol	Select			

24. Key -2:ABC pressed

	A	B	C	2	
	2nite		22		
	2day		20		
	208		200		
Input Text	207		Two		
Dear Friend, Please call me as soon as possible to					
2: 2 / to / two					
Best Use	Symbol	Select			

25. Key -2:ABC pressed

	D	E	F	3	
	D8				
	Dear				
	Don't				
Input Text	Did U C				
Dear Friend, Please call me as soon as possible to d					
D: D / d					
Best Use	Symbol	Select			

26. Key -3:DEF pressed

	D	E	F	3	
	End				
	Ence				
	Elly				
Input Text	Every 1				
Dear Friend, Please call me as soon as possible to e					
E: E / e					
Best Use	Symbol	Select			

27. Key -3:DEF pressed

Fig. 9c

11 / 16

	D	E	F	3	
	Fix				
	For				
	Friend				
Input Text	Feel like it				
Dear Friend, Please call me as soon as possible to f					
F: F / f					
Best Use	Symbol	Select			

28. Key -3:DEF pressed

	D	E	F	3	
	Fix				
	For				
	Friend				
Input Text	Feel like it				
Dear Friend, Please call me as soon as possible to fix					
Fix					
Best Use	Symbol	Select			

29. Joystick down 1

	A	B	C	2	
	And				
	Asap				
	Another				
Input Text	Alternative				
Dear Friend, Please call me as soon as possible to fix a					
A: A / a					
Best Use	Symbol	Select			

30. Key -2:ABC pressed

	D	E	F	3	
	D8				
	Dear				
	Don't				
Input Text	Did U C				
Dear Friend, Please call me as soon as possible to fix ad					
D: D / d					
Best Use	Symbol	Select			

31. Key -3:DEF pressed

	D	E	F	3	
	D8				
	Dear				
	Don't				
Input Text	Did U C				
Dear Friend, Please call me as soon as possible to fix a date					
D8: date					
Best Use	Symbol	Select			

32. Joystick down 1

	G	H	I	4	
	G2g				
	Gr8				
	Girlfriend				
Input Text	Get a life				
Dear Friend, Please call me as soon as possible to fix a date g					
G: G / g					
Best Use	Symbol	Select			

33. Key -4:GHI pressed

	G	H	I	4	
	H20				
	Hello				
	Heather				
Input Text	Have 2 go				
Dear Friend, Please call me as soon as possible to fix a date h					
H: H / h					
Best Use	Symbol	Select			

34. Key -4:GHI pressed

	G	H	I	4	
	Ic				
	Illy				
	Incorrect				
Input Text	Investig8				
Dear Friend, Please call me as soon as possible to fix a date i					
I: I / i					
Best Use	Symbol	Select			

35. Key -4:GHI pressed

Fig. 9d

12 / 16

	G	H	1	4	
	4get			44	
	4tun8			40	
	4ever			400	
Input Text	Four			4000	
Dear Friend, Please call me as soon as possible to fix a date for					
4: 4 / for					
Best Use	Symbol			Select	

36. Key -4:GHI pressed

	A	B	C	2	
	And				
	Asap				
	Another				
Input Text	Alternative				
Dear Friend, Please call me as soon as possible to fix a date for a					
A: A / a					
Best Use	Symbol			Select	

37. Key -2:ABC pressed

	A	B	C	2	
	And				
	Asap				
	Another				
Input Text	Alternative				
Dear Friend, Please call me as soon as possible to fix a date for and					
And					
Best Use	Symbol			Select	

38. Joystick down 1

	A	B	C	2	
	And				
	Asap				
	Another				
Input Text	Alternative				
Dear Friend, Please call me as soon as possible to fix a date for as soon as possible					
Asap: as soon as possible					
Best Use	Symbol			Select	

39. Joystick down 1

	A	B	C	2	
	And				
	Asap				
	Another				
Input Text	Alternative				
Dear Friend, Please call me as soon as possible to fix a date for another					
Another					
Best Use	Symbol			Select	

40. Joystick down 1

	M	N	O	5	
	M8				
	Ment				
	Meeting				
Input Text	More than				
Dear Friend, Please call me as soon as possible to fix a date for another m					
M: M / m					
Best Use	Symbol			Select	

41. Key -6:MNO pressed

	M	N	O	6	
	M8				
	Ment				
	Meeting				
Input Text	More than				
Dear Friend, Please call me as soon as possible to fix a date for another mate					
M8: mate					
Best Use	Symbol			Select	

42. Joystick down 1

	M	N	O	6	
	M8				
	Ment				
	Meeting				
Input Text	More than				
Dear Friend, Please call me as soon as possible to fix a date for another ment					
Ment					
Best Use	Symbol			Select	

43. Joystick down 1

	M	N	O	6	
	M8				
	Ment				
	Meeting				
Input Text	More than				
Dear Friend, Please call me as soon as possible to fix a date for another meeting					
Meeting					
Best Use	Symbol			Select	

41. Key -6:MNO pressed

Fig. 9e

13 / 16

Key 2 ABC

A	B	C	2		A	B	C	2		A	B	C	2		A	B	C	2	
And					B4					Call					2nite			22	
Asap					Been					Cul8r					2day			20	
Another					British					Call me					208			200	
Alternative					Balloon					Conversation					207			Two	

Key 3 DEF

D	E	F	3		D	E	F	3		D	E	F	3		D	E	F	3	
D8					End					Fix					30			33	
Dear					Ence					For					31			300	
Don't					Elly					Friend					379			3000	
Did U C					Every 1					Feel like it					366			Three	

Key 4 GHI

G	H	I	4		G	H	I	4		G	H	I	4		G	H	I	4	
G2g					H20					lc					4get			44	
Gr8					Hello					lly					4tun8			40	
Girlfriend					Heather					Incorrect					4ever			400	
Get a life					Have 2 go					Investig8					Four			4000	

Key 5 JKL

J	K	L	5		J	K	L	5		J	K	L	5		J	K	L	5	
J4F					K8					L8					50			55	
Just					Kit					Love					51			500	
Jet ski					Kiss					Less than					589			Five	
Jonathon					Keep					Listen 2 me					585			5000	

Key 6 MNO

M	N	O	6		M	N	O	6		M	N	O	6		M	N	O	6	
M8					N1					Obtw					60			66	
Ment					Never					Olly					64			600	
Meeting					Need<					Ordinary					684			Six	
More than					Next time					Over time					679			6000	

Key 7 PQRS

P	Q	R	S	7	P	Q	R	S	7	P	Q	R	S	7	P	Q	R	S	7
Pls					Qix					Rot8					See				
Pretend					Queue					Regret					Sion				
Powerful					Quote					Remember					Sme1				
Presentat8n					Question					Remind me					Soon				

P	Q	R	S	7	
70					77
707					700
799					7000
718					Seven

Fig. 10a

14 / 16

Key 8 TUV

T	U	V	8		T	U	V	8		T	U	V	8		T	U	V	8	
The					U2					Vgc					8n			88	
Tion					Use					Very					8or			800	
Tive					Uily					Voice					8teen			8000	
There					Under					Village					888			Eight	

Key 9 WXYZ

W	X	Y	Z	9	W	X	Y	Z	9	W	X	Y	Z	9	W	X	Y	Z	9
W8r					Xtra					You					Z%				
What					Xcite					Yday					Zero				
When					Xample					Yvonne					Zzzz				
Would					Xylophone					Yourself					Zentra				

W	X	Y	Z	9
90				99
900				901
Nine				9000
999				9004

Keys 1, 0, * and

1	.	,	-	?	0	+	!	'	@	a/A Caps	*	Space	#
10				100	00				000	:-)	@)>---	<):(<	<0(>><
12				One	0207				0141	:-(<	-o	> <	> ~
150				1000	0208				0131	J^	xOx	~:-o	((h))
118				1483	0800				Zero	lpl	{:-})	lCl	l0---l

Fig. 10b

15 / 16

Next	generation	of	adaptive	intelligence	interfaces
Nextel	day	delivery	forward	thinking	meeting
	time	will be	meet	proposal	dinner
	step	statistics	for	10:10am	morning
	level	we	the	way	for

Fig. 11

16 / 16




Fig. 12